# SHERPA 10AGRI





# TECHNICAL DATA SHERPA 100 AGRI

Motor

ManufacturerHondaTypeGX390Capacity9/12 kW/hpRevolutions per minute3600 rpmAdjusted amount of revolutions3000 rpm

Number of cylinders

Cooling Air Cooled
Fuel Petrol (Euro95)

Fuel tank capacity 6,11

**Drive system** Hydrostatic through 2 hydraulic wheel motors

**Speed** 0-5 (proportional) km/h\*

**Capacity data** 

Breakout force 630 kg

Tractive force 300 kg\*

Hydraulic drive- and working system 18/190 l/bar

Hydraulic tank capacity 38 l

Tires

Standard 4.00x10 - Trac profile tires


**Brakes** 

Braking system Hydrostatic on 2 rear wheels/ 2 front wheels

through chain transmission

**Steering** Skid steering

Dimensions in mm on standard tyres



A Maximum height with bucket up	2545	J Bucket angle high	53°
B Height hinge point coupling plate	2050	K Wheelbase	657
C Maximum height with bucket low	1195	L Length to coupling plate	1520
D Length + bucket	2165	M Ground clearance	121
E Bucket angle when dumping	51°	N Rear Angle	14°
F Height underside of the bucket when dumping	1480	O Turning radius	1606
G Length from front wheel to bucket when dumping	180	P Turning radius with bucket	2250
H Height bucket horizontally	1860	Q Width	760
I Hoek bak laag	26°		





## **TECHNICAL DATA SHERPA 100 AGRI**

Max. Dimensions (L mm x B mm x H mm, without bucket):

Standard 1490 x 760 x 1218


Kerb weight 539 kg (with standard tires)

A 164

#### Tipping loads (kg)\*:

Pallet forks low\*\*

B 239 C 434 Pallet forks high\*\*



A 117

\* Including driver 60kg \*\* Consider a safety factor of 30%

### **SHERPA 100 AGRI**

Thanks to the width of only 76 cm, the SHERPA 100 Agri-Line can pass through narrow passages. This makes it an ideal machine for work at riding schools and in the stables. The SHERPA 100 Agri-line is a welcome aid for the mucking out.

More information? Call us +31 412 61 33 44

Canadabaan 14 | 5388 RT Nistelrode | www.sherpaminiloaders.com







