

## MULTIONE LOADER

MT11ID



SERIES 1.1

## MT11ID



"Y" shaped knives  
"Y"-formade knivar



Paddle knives  
Spatelformade knivar



Light hammer  
Lätt hammarslaga

### MT11ID SLAGKLIPPARE MED HYDRAULISK MOTOR

Lätt slagklippare med hydraulisk motor Lätt men stabil. På slagklipparen kan man montera olika typer av verktyg och tack vare de olika tillvalen och konfigurationerna kan den tillfredsställa de mest olika behoven. Den kan monteras på maskiner med begränsat oljeflöde. Stabil och kompakt slagklippare. Montera olika typer av verktyg för att tillgodose olika behov.

#### STANDARDUTRUSTNING:

Oscillerande bottenplatta för montering • Hydraulisk motor komplett med rör och slangar (1/2 tum) • "Y"-slaga på rotorn • Nivelleringsrulle • Kit tryckreglerventil • Framhjul • överensstämmer med CE-standarder 2 rör (1- utlopp and 1-retur) L = 2000 mm. med 1/2" snabbkoppling hane • 1 dräneringsrör L = 2400 mm. med 1/2" snabbkoppling hona

#### TILLVAL:

Kit monteringsplatta (för olika modeller av lastare) • Medar på sidorna. • Rotor med spatelformade knivar, eller med lätt hammarslaga, eller med "Verticut" knivar

### MT11ID FLAIL MOWER WITH HYDRAULIC MOTOR








Light duty flail mower with hydraulic motor Light duty, but sturdy, it can mount different types of tools and thanks to the numerous options and configurations it can satisfy the most different needs. It can work on machines with limited oil flow. Sturdy and compact flail mower, it can mount different types of tools to meet the most diverse needs.

#### STANDARD EQUIPMENT:

Oscillating base connection plate • Hydraulic motor complete with pipes and hoses (1/2 Inch) • "Y" shaped knives on the rotor • Rear roller • Pressure control valve kit • Front wheels • Conforms to CE standards 2 tubes (1- outward and 1-return) L = 2000 mm. with 1/2" male quick Coupling • 1 drainage tube L = 2400 mm. with 1/2" female quick coupling

#### OPTIONS:

Connection plate kit (for various models of loaders) • Side skids. • Rotor with paddle knives, or with light hammers, or with "Verticut" knives.

MOD.			OLJEFLODE (*) OIL FLOW (*)		OLJETRYCK OIL PRESSURE											
	CM	INCH	MIN	MAX	MIN	MAX	N.	N.	N.	RPM/UPM	A: CM	A: INCH	B: CM	B: INCH	Kg	Lbs
MT11ID - 85	85	34	22	27	170	220	24	12	12	2110	95	38	85	34	158	348
MT11ID - 105	105	41	22	27	170	220	32	16	16	2110	115	45	105	41	180	397
MT11ID - 125	125	49	22	27	170	220	40	20	20	2110	135	53	125	49	201	443
MT11ID - 135	135	53	22	27	170	220	44	22	22	2110	145	57	135	53	211	465

(\*) Kan användas på oljeflöde upp till 60 liter per minut på begäran • (\*) Possibility of application on oil flow up to 60 liters / min. on demand.

A = Bredd - width • B = Arbetsbredd - working width